



ELECTRIC PUMPS

12 - Volt



EZ-8



M-150S



M-180S



M-3025

Model	Part No.	Flow Rate	Duty Cycle	Nozzle	Inlet/Outlet	Suction Pipe	Hose	Feature
EZ-8	137100-01	Up to 8 GPM (30 LPM)	15 min. On / 30 min Off	Only available w/ manual shut off nozzle	3/4 in. / 3/4 in.	3-piece, Trim-to-fit	10 ft. (3.0m) x 5/8 in.	Gas station equivalent flowrate - direct tank mounting
M-150S	110000-99 w/manual nozzle 110000-100 w/auto nozzle	Up to 15 GPM (57 LPM)	30 min. On / 30 min. Off	Available w/ Manual or Auto Shut off nozzle	3/4 in. / 3/4 in.	Adjustable to 40 in.	12 ft. (3.7m) x 3/4 in.	Convenient Spin Collar for easy installation
M-180S	110300-1 w/manual nozzle 110300-2 w/auto nozzle	Up to 18 GPM (69 LPM)	30 min. On / 30 min. Off	Available w/ Manual or Auto Shut off nozzle	1 in. / 1 in.	Adjustable to 40 in.	12 ft. (3.7m) x 1 in.	Improved flowrate and convenient Spin Collar
M-3025	133240-1 w/manual nozzle 133240-2 w/auto nozzle	Up to 25 GPM (95 LPM)	30 min. On / 30 min. Off	Available w/ Manual or Auto Shut off nozzle	1 in. / 1 in.	None	12 ft. (3.7m) x 1 in.	Highest flow, 12-volt pump, reduces time spent refueling

METERS

Model	Part No.	Flow Range	Accuracy	Inlet/Outlet	Display	Feature
MR-530	126300-02 (3/4") 126300-04 (1") 126300-06 (1.5")	5-30 GPM (19-114 LPM)	+/- 2% of reading	3/4 in., 1 in. or 1-1/2 in. NPT or BSPP available	Max. Batch Total is 4-digits	Protective bezel surrounds meter face. Easy spin knob
O1A-SERIES	113255-2 Digital Inline Meter	3-30 GPM (10-100 LPM)	+/- 2.5% of reading (accuracy can vary to +/- 5%)	1 in. NPT w/3/4 in. reducer fittings available	Max. Batch Total is 4-digits	Weighs just 12 oz. to mount at the hose end



MR-530



113255-2

SECURITY COLLAR

- Fits pre-vent cap & pump base to stop fuel theft
- Locking mechanism accepts standard Master® lock or the Master® 40 lock
- Mounts on GPI Electric Pumps w/spin collar
- Economical theft deterrent
- Synthetic polymer thermoplastic material



11080801

ACCESSORIES