

# Hitch UP Quick

# SWIFT HITCH

PATENT PENDING ©

Portable Wireless FULL COLOR  
Back-up Camera System



Hi-Resolution  
COLOR Display

Select Normal or  
Reverse Image

Magnetic Base

EASY TO USE,  
Single Hand  
Operation

Fully Automatic  
**NIGHT VISION**

[www.swifthitch.com](http://www.swifthitch.com)

© 2007 Two Loons Trading Company, All Rights Reserved. Swift Hitch® is a registered trademark of the Two Loons Trading Company. Swift Hitch® is Patent Pending.

[www.swifthitch.net](http://www.swifthitch.net) • [www.customtruckpartsinc.com](http://www.customtruckpartsinc.com)



## STEP 1 Mount

## STEP 2 View

## STEP 3 Hitch UP

### CAMERA

#### ITEMS

Imaging Sensor  
 CMOS Total Pixels  
 View Angle  
 Minimum Illumination  
 Transmission Frequency  
 Transmission Power  
 Modulation Type  
 Bandwidth  
 Power Supply  
 Battery Type  
 Consumption Current  
 Charge Time  
 Working Time  
 Unobstructed Effective Range  
 Night Vision Range  
 Dimensions(W x D x H)(mm)  
 Weight

#### SH01

1/3" CMOS  
 628 x 582 (PAL); 510 x 492 (NTSC)  
 55°  
 5Lux/F1.2 & 0Lux (IR ON)  
 ISM 2.400 MHz ~ 2.483 MHz  
 10mW/CE  
 FM  
 18 MHz  
 +12VDC  
 Rechargeable Lithium-ion Battery - 3.7 VDC  
 180mA & 230mA (IR ON)  
 Up to 2 hours  
 Up to 4 hours (3 hours IR on)  
 Up to 300 feet / 100 yards (100 meters)  
 15 feet (5m)  
 28 x 90 x 28  
 4 ounces (110 grams)

Operating Temperature  
 -10° C~+50° C/+14° F~+122° F

Storage Temperature  
 -30° C~+65° C/-22° F~+149° F

Operating Humidity  
 85%RH

Actual transmission range may vary according to weather, location, interference or building construction.

All the specifications are subject to minor change without prior notice.

### DISPLAY

LCD  
 LCD Resolution  
 Receiving Frequency  
 Intermediate Frequency  
 Demodulation Type  
 Receiving Sensitivity  
 Power Supply  
 Battery Type  
 Consumption Current  
 Dimensions (W x D x H)(mm)  
 Weight

2.5" TFT  
 960 x 240  
 ISM 2.400 MHz ~ 2.483 MHz  
 480 MHz  
 FM  
 -80dBm  
 +12V DC  
 Rechargeable Lithium-ion Battery - 3.7 VDC  
 240mA  
 80 x 38 x 130  
 8.8 ounces (250 grams)

# SWIFT HITCH

Application

Swift Hitch®

Part #

SH01

[www.swifthitch.net](http://www.swifthitch.net) • [www.customtruckpartsinc.com](http://www.customtruckpartsinc.com)

Grande Prairie 1-800-803-7785

Edmonton 1-888-422-9329

Calgary 1-877-237-7660

Port Kells, Surrey 1-800-663-5356

401